

High accuracy electric muffle furnace **SNOL 10/1300** is universal laboratory furnace, designed for materials testing, heat treatment such as hardening, loosening, normalising, ceramic and stoneware samples firing up to 1300°C. To eliminate gases or smoke that are released during thermal processing, an exhaust system may be additionally installed in the products. The furnace is an excellent fit for scientific laboratories, educational institutions, ceramic studios, medicine and industry.

DESCRIPTION

- ✓ One-piece high thermal efficiency vacuum-formed ceramic fiber chamber,
- ✓ Heating elements exposed on ceramic tubes on two sides of the chamber,
- ✓ Outside casing – metal sheet, powder painted grey,
- ✓ Door opens sideways,
- ✓ Door safety interlock switch,
- ✓ Control panel is placed in the underpart of the furnace,
- ✓ Non-programmable temperature controller – Omron E5CC,
- ✓ Ceramic bottom plates,
- ✓ Fast heating time due to low thermal mass construction,
- ✓ Low power consumption,
- ✓ Good stability and uniformity,
- ✓ 1 year warranty.

Technical data	Units	Specifications
Useful volume	Liter	10
Rated power not more than	kW	2.4
Rated supply voltage	V	230
Rated frequency	Hz	50
Number of phases	-	1
Continuous operating temperature	°C	T+10-1300
Maximum temperature	°C	1300
Working chamber material	-	Fiber muffle
Maximum heating- up time (without charge),	Min.	50
Temperature stability in working chamber at rated temperature in thermal steady state without charge not more than	± °C	1
Temperature uniformity in working space at rated temperature in thermal steady state without charge not more than	± °C	10
Furnace working chamber dimensions:		
width	mm	190
depth	mm	335
height	mm	170
Furnace dimensions:		
width	mm	500
depth	mm	710
height	mm	560
Mass (Netto)	kg	38

CONTROL:

- ✓ Temperature measurement by thermocouple type "S".
- ✓ PID electronic regulator, double digital display reference temperature and measured temperature.
- ✓ Products are equipped with high-precision digital microprocessor Omron or Eurotherm temperature controllers fitted with self-tuning and manual PID settings. The customer can select a basic or programmable temperature controller, which offers up to 32 programming segments (rate of temperature rise or decrease control, maintenance of present temperature, automatic shutdown). A wide range of devices allows selecting the most appropriate controller for your process.
- ✓ SSR control unit.

SUPPLIED DOCUMENTS:

- ✓ Furnace and temperature controller instructions,
- ✓ Electric diagram

OTHERS:

- ✓ CE marked

PACKING:

- ✓ Wooden box

OPTIONS:

- ✓ Eurotherm 3216 (non-programmable)
- ✓ Eurotherm 3208 (programmable)
- ✓ Omron E5CC-T (programmable)
- ✓ PC connection and SNOL software
- ✓ OTP (over temperature protection, non-adjustable)
- ✓ OTP (over temperature protection, adjustable Eurotherm 3216i)
- ✓ OTP (over temperature protection, adjustable Omron E5GC)
- ✓ Buzzer
- ✓ Timer (delayed furnace start)
- ✓ Ventilation hole ceramic tube (in the back side Ø17mm)
- ✓ Chimney

WARRANTY:

- ✓ One year limited warranty and later service for furnace
- ✓ Possibility to extend warranty for an additional 1 year

COUNTRY OF ORIGIN:

- ✓ Lithuania (EU country)



Administrative address
Umega Group, AB
Metalo str.5, 28216 Utena
Lithuania

Factory address
Umega Group, AB, SnolTherm unit
Plento str.3, 28104 Utena
Lithuania

Tel. +370 389 54586
sales@snoltherm.com
www.snol.com

VAT code: LT263347219
Company registration No. 126334727