

## SciQuip Benchtop Shaking Incubators

SciQuip shaking incubators are lab workhorses and provide “set and forget” programmable operating conditions and precise temperature performance for a variety of molecular biology techniques. The inner chamber is clearly visible from all angles across the room. The audible and visual alarms will alert the operator for set point deviations. The refrigerated model uses CFC Free refrigerant & is Ozone layer friendly.

### FEATURES:

- Powerful triple eccentric drive
- Heated and cooled versions
- Microprocessor control
- User-friendly sealed control panel
- Large, easy-to-read LCD display
- Timer from 1 min to 500 hrs, continuous
- Alarm
- Soft start with smooth acceleration
- Auto restart following power interruption
- SciQuip MAXI includes a printer



Flask Capacity	50ml	100ml	250ml	500ml	750ml	1000ml
MINI	9	9	5	-	-	-
MIDI	18	18	10	9	5	4
MAXI	23	23	12	9	7	5



Model	Incu-Shake MINI (includes platform)	Incu-Shake MIDI (includes platform)	Incu-Shake MAXI (includes platform)
Temperature Range	Ambient +5 to 70°C	Ambient +5 to 70°C	4°C to 70°C
Temperature Accuracy	±0.1°C	±0.1°C	±0.1°C
Temperature Uniformity	≤± 1°C @ 37°C	≤± 1°C @ 37°C	≤± 1°C @ 37°C
Shaking speed (rpm)	25 to 600	25 to 600	25 to 600
Volume	34 Litres	63 Litres	69 Litres
Stroke	Ø1-50mm Stepless Adjustment		
Shaking Mode	Orbital		
Tray (WxD)	280x220mm	340x370mm	400x370mm
Timer	1 min to 500hrs	1 min to 500hrs	1 min to 9999mins
Internal Dimensions (WxDxH)	340 x 300 x 175 mm	410 x 440 x 295 mm	490 x 470 x 320 mm
External Dimensions (WxDxH)	440 x 410 x 390 mm	600 x 580 x 520 mm	774 x 740 x 610 mm
Packing Dimensions (WxDxH)	510 x 480 x 560 mm	670 x 650 x 680 mm	844 x 810 x 770 mm
Gross Weight (kg)	54	94	132
Power (W)	280	550	700
Warranty	2 years	2 years	2 years